

POSITIVE IMPRESSION DUE TO EXCEPTIONAL PRINTS.

Do you need reliable printing and copying results of the highest quality in a minimum of space? If so, there is no alternative to the 4006ci/5006ci/6006ci A3 colour multifunctional systems. You'd be hard pushed to achieve better results thanks to the print resolution of 1,200 x 1,200 dpi, newly developed toner and advanced colour technology. The innovative and touch-sensitive colour touch display makes it even easier to operate the systems.

The systems also score highly when it comes to the environment: if required, blank pages can be automatically filtered out when scanning and copying. This can result in great savings, particularly with the 270-sheet dual scan original feeder* for fast scanning in a single operation and gentle handling of original documents. In addition, you can also integrate your own customised software solutions* via the HyPAS interface.



DIGITAL MULTIFUNCTIONAL
 COLOUR SYSTEM

4006ci / 5006ci 6006ci

Copy / Print / Scan / Fax
 A3

HIGHLIGHTS:



Professional printing: The option to process various paper thicknesses in one go enables you to also create professional handouts and presentations. In addition, the versatile printer driver offers intuitive tools for the further optimisation of colour reproduction.



Flexible paper management: Up to 7,150 sheets* of different paper types and paper weights can be fed. The printed pages are then processed via an internal* or external finisher*, also with an optional punch unit. The brochure finisher* can also output tri-folding for letters or flyers in addition to A5 and A4 brochures. Furthermore, the multi tray* for the brochure finisher* ensures that the documents of a work group do not get mixed up. Our standard paper cassettes are also naturally equipped with our new soft close feature.



Simplest operation: The large 9-inch colour touch display with a picture diagonal of 22.86 cm makes it easier to execute the wide range of functions on offer. The home menu, which you can adapt to suit your requirements, is particularly helpful here. In addition, the optional Fiery® Controller offers top productive performance when it comes to processing and reproducing challenging colour print data.



Maximum security: The 'Private Printing' function allows a PIN code to be assigned to print jobs and ensures that print jobs can only be activated by authorised users. The Data Security Kit* encrypts your hard disk data and deletes it securely after use.

4006ci / 5006ci / 6006ci

TECHNICAL DATA



| | | | | | |
|------------------------------|--|---|--|--|--|
| General | | Print system | | Fax system 12 | |
| Type | Desktop | Type | Integrated within the system | Abbreviated dial | 2,000 numbers |
| Function | Copy, print, scan, optional: fax | Print format | A6R-SRA3 | One touch dial | 1,000 numbers |
| Print technology | Laser colour and b/w | Print resolution | 600 x 600 dpi, max 1,200 x 1,200 dpi | Group dial | 500 numbers |
| Original format | max A3 from platen glass | Processor | Freescale QorIQ T1024 (Dual Core) 1.2 GHz | Operating systems | Windows XP, Vista, Windows 7/8.1/10, Server 2003/2008 R2/2012 R2 |
| Copy/print speed | 4006ci: max 40 A4 pages/min and max 20 A3 pages/min in colour and b/w, 5006ci: max 50 A4 pages/min and max 25 A3 pages/min in colour and b/w, 6006ci: max 55 A4 pages/min and max 27 A3 pages/min in colour and b/w and max 60 A4 pages/min and max 30 A3 pages/min in b/w | Interfaces | USB 2.0, 10/100/1000BaseTX, USB host | Functions | Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception |
| 1st page (Copy/Print) | Colour: 5.9/6.5 seconds*, b/w: 4.5/5.1 seconds* (4006ci), Colour: 4.8/5.4 seconds*, b/w: 3.7/4.3 seconds* (5006ci), Colour: 4.4/5.1 seconds*, b/w: 3.4/3.8 seconds* (6006ci) | Network protocols | TCP/IP, Net BEUI | Options | |
| Warm-up time | 17 seconds* | Operating systems | Windows XP, Vista, Windows 7/8.1/10, Server 2003/2008 R2/2012 R2, Novell NetWare***, Linux, Mac OS 10.5 | Original feeder | DP-7100 document processor with automatic reverse function (A6R-A3, capacity: 140 sheet A4, paper weight 35-160 g/m ²), DP-7110 document processor with simultaneous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²) |
| Copy resolution | 600 x 600 dpi | Emulations | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PDF, PRESCRIBE IIc | Platen cover | Platen cover type E (if document processor is not installed) |
| Greyscales | 256 | Functions | Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, barcode printing speed mode), barcode printing, Mobile Print (Android/iOS)/Apple AirPrint | Finisher | DF-7100 internal finisher (capacity: 500 sheet A4, stapling max 50 sheet A4), DF-7120 (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-7110 (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7120 hole punch unit for DF-7100, PH-7C hole punch unit for DF-7120/7110, BF-730 brochure module for DF-7110 (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-7110 |
| Paper feed | 2 x 500 sheet universal cassettes (magasin 1: A6R-A4, magasin 2: A6R-SRA3 [320 x 450 mm]), 150 sheet multi-bypass (A6R-SRA3, Banner [305 x 1,219 mm]), SRA3 and banner only for printing | Scan system | | Job Separator | JS-7100: 100 sheet |
| Paper weights | Universal cassette 52-300 g/m ² , multi-bypass 52-300 g/m ² , duplex 64-256 g/m ² | Scan type | CCD colour and b/w | Paper feed | PF-7100 (2 x 500 sheet universal cassettes [A5R-SRA3]), PF-7110 (2 x 1,500 sheet large capacity cassette [A4]), PF-7120 (3,000 sheet large capacity tray [A4], side deck) |
| Paper output | 500 sheet A4 | Scan format | max A3 | Other options | Scan extension kit (A), Data security kit (E), Internet fax kit (A), Card authentication kit (B), Keyboard holder 10, Banner guide 10, UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, IB-35 WLAN card, DT-730 (B) Document tray, NK-7100 Numeric Keyboard (10 keys), cabinet no. 76, Fiery® Controller (Printing System 15) |
| System memory | 4 GB RAM, 8 GB SSD/320 GB HDD** | Scan speed | max 100 (simplex) or 180 (duplex) A4 originals/min in colour and b/w with DP-7110 (300 dpi) | *Depending on operating status. | |
| Continuous copying | 1-999 copies | Scan resolution | 200 dpi, 300 dpi, 400 dpi, 600 dpi | **For copy, print, scan, fax ***optional | |
| Zoom | 25 %-400 % in steps of 1 % | Scan mode | Photo, text, photo/text, suitable for OCR | Specifications subject to change without notice. | |
| Functions | Adjustable colour touch screen (9 inch), duplex, 1,000 management codes, skip blank pages etc. | Scan resolution | 200 dpi, 300 dpi, 400 dpi, 600 dpi | Image shows machine with optional accessories. | |
| Dimensions/Weight | | Scan mode | Photo, text, photo/text, suitable for OCR | The 4006ci, 5006ci and the 6006ci are manufactured in accordance with the requirements of the Energy Star Program. | |
| Dimensions | 790 x 602 x 665 mm (H x W x D) | File types | TIFF, PDF, PDF/A, high compression PDF, encrypted PDF, JPEG, XPS, Open XPS | | |
| Weight | approx. 95 kg | Interfaces | 10/100/1000BaseTX | | |
| Environment | | Network protocol | TCP/IP | | |
| Mains voltage | 220/240 V, 50/60 Hz | Network protocol | TCP/IP | | |
| Power consumption | approx. 1,750 W max, approx. 730/860/960 W in operation (4006ci/5006ci/6006ci), approx. 60 W in stand-by mode, approx. 1 W in sleep mode, TEC value: 1.95/2.50/3.14 kWh/week (4006ci/5006ci/6006ci) | Operating systems | Windows XP, Vista, Windows 7/8.1/10, Server 2003/2008 R2/2012 | | |
| Safety | GS/TÜV, CE | Functions | Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP | | |
| Fax system 12 | | Compatibility | | | |
| | | Super G3 | | | |
| | | Original format | | | |
| | | max A3 | | | |
| | | Modem speed | | | |
| | | 33.6 kbps | | | |
| | | Transmission speed | | | |
| | | 3 seconds or less using JBIG | | | |
| | | Compression method | | | |
| | | JBIG, MMR, MR, MH | | | |
| | | Fax resolution | | | |
| | | Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi | | | |
| | | Fax memory | | | |
| | | 170 MB | | | |

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

UTAX Norderstedt
www.utax.com



Your UTAX-dealer