

THE SMALL POWER PACKAGES FOR THE WORKPLACE.

These compact and powerful black and white printers from UTAX will easily impress you: Simply switch the printer on, and after only a few seconds, you will be producing your first printout. With printing speeds of between 45 and 60 A4 pages per minute and up to 1200dpi resolution, these printing systems are essential for flexibility in your everyday office life. Thanks to their optimised consumption levels, they also help to improve energy efficiency in your company. Get these experts on board and conserve resources, protect the environment and, above all, go easy on your budget!



P-4531DN
P-5031DN
P-5531DN
P-6031DN

B/W-PRINTER / A4

HIGHLIGHTS:



Flexibility and productivity: The ability to process different paper formats from A6 to A4, a high paper capacity of up to 2,600 sheets* and paper weights of 60 to 220 g/m² ensure dynamic performance. This way, you always remain ahead of the game.



Optimal connectivity: The printing systems can be quickly integrated into your workplace network thanks to numerous connection options such as LAN or WLAN*, IEEE 1284* or USB 2.0.



High storage capacity: The optional hard drives (32 or 128 GB) store large quantities of data and process your jobs at an impressive speed, without burdening the network. The systems support SD cards* with up to 32 GB storage space and offer a large system memory that can be expanded up to a maximum of 2 GB*.



State-of-the-art security concept: The optional Data Security Kit (E) and support of a range of security protocols ensure your data is protected. This means you're always on the safe side.



Economical operation: The systems are notable for their low power consumption and wonderfully quiet operation. Not only does this save you money, it also gives you peace of mind.

P-4531DN / P-5031DN P-5531DN / P-6031DN

TECHNICAL DATA

General		General		Environment	
Type	Desktop	Operating systems	Windows XP, Vista, Windows 7/8.1/10, Server 2003/2008 R2/2012 R2, Linux, Mac OS 10.5	Noise level	<i>P-4531DN:</i> approx. 52.8 dB(A) in operation, approx. 27.1 dB(A) in stand-by mode (ISO 7779/9296) <i>P-5031DN:</i> approx. 53.2 dB(A) in operation, approx. 26.9 dB(A) in stand-by mode (ISO 7779/9296) <i>P-5531DN:</i> approx. 54.7 dB(A) in operation, approx. 27.1 dB(A) in stand-by mode (ISO 7779/9296) <i>P-6031DN:</i> approx. 55.2 dB(A) in operation, approx. 27.1 dB(A) in stand-by mode (ISO 7779/9296)
Function	Print	Emulations	PCL6 (PCL5e, XL), KPD (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS	Safety	GS/TÜV, CE
Print technology	Laser b/w	Functions	Duplex, 100 management codes, USB direct printing, private printing, barcode printing, Google Cloud Print	Options	
Print format	max A4	Dimensions/Weight		Paper feed	max 4 x PF-320 (500 sheet universal cassette [A5R-A4, 60-120 g/m ²]), max 1 x PF-3100 (2,000 sheet large capacity cassette [A5R-A4, 60-220 g/m ²]), PB-325 (Attachment Kit is required for PF-3100)
Print speed	<i>P-4531DN:</i> max 45 A4 pages/min, duplex: max 32 A4 pages/min <i>P-5031DN:</i> max 50 A4 pages/min, duplex: max 36 A4 pages/min <i>P-5531DN:</i> max 55 A4 pages/min, duplex: max 39.5 A4 pages/min <i>P-6031DN:</i> max 60 A4 pages/min, duplex: max 43 A4 pages/min	Dimensions	<i>P-4531DN:</i> 285 x 380 x 410 mm (H x W x D) <i>P-5031DN/P-5531DN/P-6031DN:</i> 320 x 380 x 410 mm (H x W x D)	Paper output	max 1 x PT-320 (1 x 250 sheet output tray, except P-4531DN)
1st page	<i>P-4531DN:</i> 5.9 seconds* <i>P-5031DN:</i> 6.2 seconds* <i>P-5531DN:</i> 6.6 seconds* <i>P-6031DN:</i> 4.9 seconds*	Weight	<i>P-4531DN:</i> approx. 14.5 kg <i>P-5031DN/P-5531DN/P-6031DN:</i> approx. 15.5 kg	Other options	Data Security kit (E), Card authentication kit (B), UG-33 ThinPrint® kit, IB-32 B IEEE1284 parallel, IB-50 Gigabit Ethernet card, IB 36 / IB-51 WLAN card, HD-6 SSD (32 GB), HD-7 SSD (128 GB), cabinet no. 67 (high), cabinet no. 71 (low)
Warm-up time	<i>P-4531DN:</i> 15 seconds* <i>P-5031DN:</i> 20 seconds* <i>P-5531DN/P-6031DN:</i> 25 seconds*	Environment		*Depending on operating status.	
Print resolution	1,200 x 1,200 dpi	Mains voltage	220/240 V, 50/60 Hz	**P-4531DN: Supports only up to A5R	
Greyscales	256	Power consumption	<i>P-4531DN:</i> approx. 1,218 W max, approx. 594 W in operation, approx. 10 W in stand-by mode, approx. 0.9 W in sleep mode, TEC value: 2.16 KWh/week <i>P-5031DN:</i> approx. 1,222 W max, approx. 636 W in operation, approx. 11 W in stand-by mode, approx. 0.9 W in sleep mode, TEC value: 2.41 KWh/week <i>P-5531DN:</i> approx. 1,238 W max approx. 675 W in operation, approx. 11 W in stand-by mode, approx. 0.9 W in sleep mode, TEC value: 2.74 KWh/week <i>P-6031DN:</i> approx. 1,238 W max, approx. 684 W in operation, approx. 11 W in stand-by mode, approx. 0.8 W in sleep mode, TEC value: 2.96 KWh/week	Specifications subject to change without notice.	
Paper feed	1 x 500 sheet universal cassette (A6R-A4)**, 100 sheet multi-bypass (A6R-A4)			Image shows machine with optional accessories.	
Paper weights	Universal cassette 60-120 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-120 g/m ²			The P-4531DN, P-5031DN, P-5531DN and the P-6031DN are manufactured in accordance with the requirements of the Energy Star Program.	
Paper output	<i>P-4531DN:</i> 250 sheet A4 <i>P-5031DN/P-5531DN/P-6031DN:</i> 500 sheet A4				
System memory	512 MB RAM, (max 2 GB RAM)				
Processor	Cortex-A9 / 1200 MHz				
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), SD slot				
Network protocols	TCP/IP, NetBEUI				

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



Your UTAX-dealer